

**SOTRES Group** designs and manufactures bentoniteslurry process equipment (desanders) adapted to customers' expectations.

These units are very popular on special foundations (slurry walls, deep boring, jet grouting, tunneling...).

## **PURPOSE**


- Bentonite preparations
- Bentonite desanders
- Bentonite desilters



Desander type D120-50
Double hydrocyclone
120 m³/h on primary stage
50 m³/h on secondary stage

## **SOLUTION**

- Drilling mud preparation and regeneration.
- Capacity: from 45 m³/h to 500 m³/h mobile desanders realisation.
- Customized design adapted to customer wishes.
- Compact solutions easy to plug in/plug out and remove.



- Scalping: eliminates > 5 mm particles.
- Pumping tanks and Access.
- Primary hydrocyclone.
- Dewatering.
- Secondary cycloning.
- Desilting machine to extract the silty muck. Ultrafines removal.
- Storage tank.

Elimination of the **200 µm/5 mm** particles.

Elimination of the  $30 \mu m/200 \mu m$ .

## **COMPLEMENTARY PROCESS EQUIPMENTS**

The bentonite slurry treatment plant can be equipped with other units required by customer application:

- ► Flocculent preparatory system.
- Centrifuge unit.
- Press filter.



Bentonite sludge preparator system.



Desander type D500-500 with screening and double hydrocyclone.
500 m³/h on primary stage
500 m³/h on the secondary stage

## **STRONG ASSETS**

- Overall of usual yield, with optimal desanders efficiency.
- Easy to install, easy to move...
- Certified for health and safety regulations.
- Versatile solution able to match for every demanding job site: Cube without silo, Superstructure with silos...



Superstructure version « Le Grand Paris » Desilter D550-550 (550 m³/h on the primary 550 m³/h on the secondary)



Cube without silo version.



Desander type D500-500.